


HPRT-HT-300 Datasheet

- Direct thermal and thermal transfer printing applications
- High printing speed(5IPS), fast label throughput
- Double type sensors allowing to support broad range of labels
- Dual-wall frame, robust and sturdy structure
- TPH special designed overcoat, endure large printing volume
- ZPL and TSPL programming language
- Bundled with Bartender label designer software & Seagull Windows Driver



300-meter Ribbon Capacity



Optional cutter module



Optional Peeler module



Specification

Item	Parameter		
	HT300	HT330	
Printing	Printing Method	Thermal transfer/Direct thermal	
	Resolution	203dpi(8dots/mm) 300dpi(11.8dots/mm)	
	Printing Speed	5IPSMAX 4IPSMAX	
	Printing Width	108mm Max 106mm Max	
	Printing Length	15mm - 1200mm	
Processor	32 bit RISC CPU		
Memory	RAM	32MB	
	Flash	16MB	
Detection	Adjustable reflective sensor,Fixed transmissive sensor(Central aligned), Head-up sensor, Ribbon end sensor		
Media	Types	Roll-fed or Fan-fed,Die-cut or Continuous label,Tag stock,Continuous receipt paper	
	Width	0.79''(20mm) – 4.65''(118mm)	
	Thickness	0.003''(80um) – 0.007''(180um)	
	Label Roll Diameter	5''(127mm)	
Ribbon	Core Diameter	1''(25.4mm),1.5''(38mm),3''(76.2mm)	
	Types	Wax,Wax/Resin,Resin	
	Width	1.33''(33.8mm) – 4.33''(110mm)	
	Length	984'(300m)	
Programming Language	TSPL, ZPL Simulation		
	Label Design	Bartender UltraLite	
Software	Driver	Windows Vista/7/8.1/10, Server 2012/2016/2018	
	SDK	Windows, MacOS, Android, iOS	
	Resident Fonts	8, 12, 16, 24, 32 and OCR A & B 90°, 180°, 270° rotatable. 10 times maximum expandable in horizontal and vertical directions.	
Resident Fonts	Bitmap Fonts	Monotype CG Triumvirate™ scalable true type font	
	TTF fonts		

Download Fonts	Bitmap fonts	90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable
	TTF fonts	90°, 180°, 270° rotatable
	Asian fonts	16x16, 24x24. Traditional Chinese, Simplified Chinese, Japanese, Korean
Code Pages		39
Barcode	1D	20
	2D	PDF417, Maxicode, DataMatrix, QR Code, Aztec
Interfaces	Standard	USB,RS232C,Ethernet
	Optional	Bluetooth,WiFi
Control Panel	Two bi-color status LEDs:Ready,Status	
	Control key:Feed	
Power Adopter	AC/DC switching power adapter	
	Input: AC 100-240V, 50/60Hz Output: DC 24V/2.5A, Peak7A	
Environment	Operation	41°F(5°C)-104°F(40°C)
	Storage	30%-85%,non-condensing
		-4°F(-20°C)-122°F(50°C)
Physical Characteristics	Dimension(L*W*H)	285*226*171mm
	Weight	2.26kg,excluding consumables
Options & Accessories	External label roll holder for 8'' (203mm) OD label rolls Cutter module Peeler module	
Agency Approvals	FCC,CE	



OGA International (Head Office)
546 Sukhonthasawat Rd, Ladphrao Sub-District
Ladphrao District, Bangkok 10230, Thailand
Tel : 02 025 8888 Fax : 02 025 8880
Call Center : 02 025 8889



sales@oga.co.th



OGA International



@OGAGroup