LNX3

3-Inch Mobile Printer

Drive productivity, improve inventory management, and customer service by giving your workers a leading advantage in challenging work environments to help achieve your operational goals.

Durable, rugged direct thermal printer with intuitive set-up and interface for premium printing performance.

The LNX3 mobile label and receipt printer brings the power and reliability of Honeywell printers into a durable, lightweight, direct thermal printer meeting or exceeding industry printer specifications. This three-inch, feature-packed, high-capacity label and receipt printer gives the right technology for your business's rapidly changing work environments.

Compact enough to carry or wear during a full work shift, equipped with seamless Wi-Fi and Bluetooth® connectivity, and leading print speeds up to 5 IPS, this printer supports large-volume label and receipt printing requirements in longer intervals helping boost productivity. Keep printing through demanding environments with a long-lasting 2800mAH hot-swap battery allowing for extended operating and standby time.

Effortlessly connect with MFi, NFC pairing, and both Bluetooth and Wi-Fi options. Print from almost any device with Windows®, iOS, and Android™ compatibility.

Enable greater mobility and capability with optional accessories, including a IP54 case with belt clip or shoulder strap, battery charger, spare battery, and more.

FEATURES AND BENEFITS

Certification to IP54, withstands tumbles up to 0.5 m (1.5 ft) and drops up to 1.8 m (5 ft) with protective case for maximum durability.

Powered by a 2800mAH hot-swap battery, easily swap the battery without losing connectivity or re-setting the printer.

MFi certified for iOS and Bluetooth, and NFC to conveniently connect to smart devices.

2.4-inch LED color screen and single hand media loading door design simplifies setup and maintenance.

Comprehensive printer command language support, such as ZPL-II, ESC/P, CPCL, XSim, ESC/POS, and more for easier printing.

Honeywell

LNX3 Mobile Printer Technical Specifications

MECHANICAL

Dimensions:
137 mm L x 117 mm W x 55 mm H
(5.31 in L x 4.53 in W x 2.05 in H)

Weight: 0.5 kg (1.1 lbs) (with paper roll and battery)

Display Size: 6.1 cm (2.4 in)

ENVIRONMENTAL

Meets IP54 dust and water ingress rating

Drop: 1.8 m (6 ft) with protective case

Tumble: 1000 cycles at 0.5 m (1.6 ft)

Operating Temperature:
-15°C to 55°C (5°F to 131°F)

Storage Temperature:
-20°C to +70°C (-4°F to +158°F)

Charging Temperature:
0°C to 45°C (32°F to 113°F)

Humidity:
10% to 90%, non-condensing

SYSTEM ARCHITECTURE

Product:
LNX3-0: NFC, USB C, BT5.0
LNX3-1: NFC, USB C, BT5.0, Wi-Fi

Printing Modes: Direct thermal printing

Processors: Arm® Cortex®-A7, up to 792 MHz

Memory:
RAM: 256 MB
Flash: 256 MB

Standard Battery:
Rechargeable, removable, 7.4V Li-Ion, 2800mAh
Supports 1 minute hot swap
Integrated fuel gauge to monitor battery charge levels
Recharging: ≤3.5H

Battery Endurance:
Bluetooth SKU: 118 m (387 ft)
Bluetooth & Wi-Fi SKU: 96 m (314 ft)

Memory:
RAM: 256 MB
Flash: 256 MB

AC Adapter: 100 to 240 VAC 5VDC@2.0A

PRINT AND MEDIA SPECIFICATIONS

Printing Resolution: 203 dpi (8 dots/mm)

Printing Speed: 50 - 127 mm/s (2-5 in per second)

Media Roll Width: 43 - 80 mm (1.7 - 3 in)

Media Length: 20 - 1016 mm (0.78 - 40 in)

Maximum Roll Capacity: 43 mm (1.69 in) outside diameter

Media Thickness: 0.06 - 0.18 mm (2 to 7 mils)

CONNECTIVITY

Standard:
USB 2.0, Type C

USB virtual COM port for diagnostic information

NFC, for quick pairing

Bluetooth 5.0 + BLE; Made for iPhone/iPad certified

Optional:
Wi-Fi LAN 802.11 a/b/g/n and Bluetooth with dual radio mode

SOFTWARE

Programming Language: ESC/P (Line print and easy print modes), ZPLII, CPCL, ESC/POS, XSim

- Yushi printer tool configuration utility
- SDKs for Android, iOS and Windows
- InterDriver printer drivers for Windows PCs

CHARACTER SETS

ESC/P (Easy Print, Line Print):
Standard: Arabic, Cyrillic, Greek, Thai and Hebrew

CPCL
Standard: Latin
Optional: Simplified Chinese, traditional Chinese, Japanese, Korean, Arabic and Thai

ZPL-II
Standard: Latin
Optional: Simplified Chinese, traditional Chinese, Japanese, Korean, Arabic and Thai

XSim
Standard: Latin

ESC/POS Most Codepage

SHIPS WITH

- Printer with standard battery
- Universal AC charger with USB cable
- Plastic belt clip
- Quick-start guide
- CD (printer driver and printer configuration tool)
- Regulatory sheet

BARCODE SYMBOLOGIES/GRAPHICS

ESC/P
1D: Code 39, Codabar, interleaved 2 of 5, code 128, EAN-18, UPC-A, EAN-8, EAN-13
2D: Aztec, PDF417, QR code
Graphics: Bitmap graphics, compressed graphics

ZPL
1D: Code11, interleaved 2 of 5, code 39, EAN-8, UPC-E, code 93, code128, EAN-13, industrial 2 of 5, standard 2 of 5, ANSI Codebar, LOGMARS, MSI, Plessey, UPC/EAN Extensions, UPC-A
2D: Aztec, PDF417, UPS MaxiCode, QR code, data matrix
Graphics: Bitmap graphics, compressed graphics

CPL
1D: Codabar, Code 39, Code 128, interleaved 2 of 5, UPC-A, UPC-E, EAN13, EAN8, EAN/JAN-13, EAN/JAN-8, Code 93/Ext. 93, I2OF5C, German post code, MSI/Plessy
2D: Aztec, PDF417, MaxiCode, QR code
Graphics: Bitmap graphics, compressed graphics

XSim
1D: Codabar, code 39, code 128, EAN/UPC interleaved 2 of 5
2D: PDF417, QR code
Graphics: Bitmap graphics, compressed graphics

ESC/POS
1D: UPC-A, UPC-E, EAN13, EAN8, code 39, interleaved 2 of 5, Codabar, code 93, code 128, code 11, MSI
2D: PDF417, MAXICODE, QR code
Graphics: Bitmap graphics

ACCESSORIES

- Belt clip (in standard packing)
- Printer single charge base
- Quad battery charger
- Carrying case
- Spare battery
- Power adapter with USB cable (in standard packing)
- Adapter/12V-24V (vehicle battery charger)

For a complete listing of all compliance approvals and certifications, please visit www.honeywell.com/PSScompliance

For a complete listing of all supported barcode symbologies, please visit www.honeywell.com/PSS-symbologies

Apple, Android, iOS, iPhone, iPad, Windows, Bluetooth, and Arm Cortex are trademarks or registered trademarks of their respective owners.

OGA GROUP
OGA International (Head Office)
546 Sukhonthasawat Rd, Ladphrao Sub-District
Ladphrao District, Bangkok 10230, Thailand
Tel : 02 025 8888 Fax : 02 025 8880
Call Center : 02 025 8889
sales@oga.co.th
OGA International
@OGAGroup