

UROVO

UROVO DT50S

Specifications



UROVO Technology Co., Ltd.



Specifications

Performance	Model	UROVO DT50S
	O.S.	Android 11(R)
	Processor	Octa-core 2.45GHz
	Memory	RAM: 4GB ROM: 64GB RAM: 8GB ROM: 128GB (optional)
	Extended memory	Micro-SD card, Up to 256 GB
Basic specifications	Dimensions	162.6*76*13.6mm
	Weight	265g
	Display	5.7 inch display, 720*1440
	Touch Screen	Ultra sensitive capacitive touch panel, support multi-touch, works with gloves and wet fingers
	Main battery	Capacity: 3.85V 4300mAh, 6000mAh (optional)
	RTC	The system time could be backed up for 10 minutes after the battery is removed
	Audio	Dual-Microphone (noise cancellation), Speaker (1.5W, 100dB @ 10cm), Receiver, 3.5mm audio jack
	Buttons	PWR button, Vol+/- button, scan button*2, custom button
	Notifications	Audible tone; multi-color LEDs; vibration
	Camera	Front 5MP, Rear 13MP with flash
	Sensors	Light + Accelerator+ Proximity + Geomagnetic + Gyro (optional)
	Fingerprint	Capacitive Fingerprint Module (optional)
	Scanning	Professional scan engine Support international standard 1D/2D barcode; Support barcode displayed on screen and colored barcode;
	Slots	Micro SD/TFx1 , Nano- SIMx2
Interfaces	USB TypeC*1, support OTG, support USB3.1; Bottom POGO PIN*2, back POGO PIN* 9	
Network Connections	WWAN	4G/ 3G/ 2G Dual-SIM, Dual-Standby
	Bluetooth	BT5.0 + BLE
	WIFI	2.4G/5G, IEEE 802.11a/b/g/n/ac/d/e/h/i/k/r/v/w Roaming: 802.11r /OKC/ PMKID caching, 802.11ax ready
	NFC	RFID 13.56MHz , ISO15693、 ISO14443A/B 、 Mifare、 Felica
	Positioning	Dual-band GPS (L1+L5) 、 A-GPS、 BeiDou、 GLONASS 、 Galileo
Environment	Operating Temp.	-20°C to 60°C
	Storage Temp.	-40°C to 70°C
	Humidity	5%RH ~ 95%RH (No condensation)
	Drop Specification	Multiple 1.5 m drops to concrete at room temperature



	Sealing	IP67
	ESD	+/-15kv Air; +/-8kv contact

Data Capture Specifications

1) Camera

Rear Camera	
functions	Flash light (700mA), Auto-focus, Video, PDAF
Pixels	13MP
Front Camera	
Pixels	5MP, Fixed-focus,

2) Scan Engine

	2D Imager Engine Specifications
Scan Angels Tilt	360°
Scan Angels Pitch	±60°
Scan Angels Skew	±60°
Laser type	Class II
Fill-in light	White LED, soft light
Barcodes support	Linear: Codabar, Code 11, Code 128, Code 2 of 5, Code 39, Code 93 and 93i, EAN/JAN-13, EAN/JAN 8, IATA Code 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, GS1 Databar, UPC-A, UPC E, UPC-A/EAN-13 with Extended Coupon Code, Coupon GS1 Code 32(PARAF), EAN-UCC Emulation, GS1 Data Bar 2D Stacked: Codablock A, Codablock F, PDF417, MicroPDF417 2D Matrix: Aztec Code, Data Matrix, MaxiCode, QR Code, Chinese Sensible (Han Xin), Grid Matrix, Dot Code Postal: Australian Post, British Post, Canadian Post, China Post, Japanese Post, Korea Post, Netherlands Post, Planet Code, Postnet

3) RFID(HF)

RFID	HF
Protocol	ISO15693、ISO14443 A/B、Mifare、Felica
Frequency	13.56MHz
Mode	Card Emulation、Peer-to-Peer、Reader
Reading Range	Read distance 0-6cm (ISO15693), 0-4cm(ISO14443A/B)

Network Connections

1) Positioning

Positioning	Specification
Mode	GPS、A-GPS、BEIDOU、GLONASS、Galileo
Frequency	GPS (L1+L5) , BeiDou (B1 1.561GHz) , GLONASS(L1 1.602GHz), Galileo (E1 1.589 GHz / E2 1.561 GHz)



Cold start time	Less than 40s
Max channel	31 channel
sensitivity	-130dB(SNR value 40dBHz)
Precision	2~3 Meters (open space)

2) Wireless LAN

WLAN	Specification
Protocol	IEEE 802.11a/b/g/n/ac/d/e/h/i/k/r/v/w (2.4G/5G dual band WIFI) IEEE 802.11ax ready
Frequency	2.4G、5G
Working Channels	CH1~CH13, CH34-CH140, CH149~CH165, depends on country (region)
Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA3 Personal (SAE); WPA/WPA2 Enterprise (TKIP and AES); WPA3 Enterprise 192-bit mode (GCMP-256) - EAP-TLS; Enhanced Open (OWE)
Fast roaming	PMKID caching; Cisco CCKM; 802.11r(Over-the-Air); OKC, WIFI roaming threshold could be set

3) Wireless WAN

WAN	Specification
Mode	Dual-SIM, Dual-Standby
Frequency Band (Europe and Asia)	TD-LTE(B34/B38/B39/B40/B41) FDD-LTE(B1/B3/B5/B7/B8/B20) WCDMA(B1/B2/B4/B5/B8) TD-SCDMA(B34/B39) CDMA2000 1x EV-DO Rev.A BC0 (800MHz) CDMA1x GSM/EDGE/GPRS(850/900/1800/1900)
Frequency Band (America)	TD-LTE(B41) FDD-LTE(B1/B2/B3/B4/B5/B7/B8/B12/B17/ B28A/B28B) WCDMA(B1/B2/B4/B5/B8) CDMA2000 1x EV-DO Rev.A BC0 (800MHz) CDMA1x GSM/EDGE/GPRS(850/900/1800/1900)

4) Wireless PAN

BT	Specification
Mode	BT5.0 + BLE



OGA International (Head Office)
546 Sukhonthasawat Rd, Ladphrao Sub-District
Ladphrao District, Bangkok 10230, Thailand
Tel : 02 025 8888 Fax : 02 025 8880
Call Center : 02 025 8889



sales@oga.co.th



OGA International



@OGAGroup